

NORDIK

MOVE

PRODUCT NUMBER:
N-Nordik MOVE
1100



INCLUDED :

- 3 ADAPTER BLADES 3/4" X 6" X 44"
- 3 STEEL CLAMP BARS 1/2" X 4" X 44"
- 11 CARBIDE BLADES «NORDIK MOVE»
- 22 SCRAPER BOLT 5/8" X 2 1/2"
- 22 HEXAGONAL BOLTS 5/8" X 3 1/2"
- 44 STOVER LOCK NUTS 5/8"

SPECIFICATIONS:

- MADE IN STEEL 1020 AND RUBBER DURO RESISTANT TO -57°C (-70°F)
- VIRGIN CARBIDE INSERT «GBN» DESIGN
- HARDNESS OF CARBIDE MIN. 88 TO 89 ROCKWELL "A"
- TRANSVERSE RUPTURE STRENGTH 351 000 PSI
- HIGH QUALITY BRAZING SHEAR STRENGTH 102 000 PSI

INSTALLATION :

1. INSTALL THE ADAPTER BLADES (WITH SCRAPER BOLTS 5/8" X 2 1/2" AND NUTS 5/8")
2. INSTALL CARBIDE BLADES AND STEEL CLAMP BARS (WITH HEXAGONAL BOLTS 5/8" X 3 1/2" AND STOVER LOCK NUTS 5/8")



NORDIK MOVE

PRODUCT NUMBER:
N-Nordik MOVE
1100

INSTALLATION:

